



JBRFR24IGX

24" BUILT-IN REFRIGERATOR COLUMN (RIGHT-HAND DOOR SWING)

Open your eyes to a column that redefines refrigeration. Satisfy cravings in the quiet cool, which is controlled by precise calibration from three sensors. Revel in the daring Obsidian interior illuminated by light that comes alive as you touch the controls. Go ahead—intoxicate your senses. Open wide.

FEATURES

OVER 250 CONFIGURATIONS

Freezer or refrigerator. Left-hand or right-hand swing. One, two, three columns in a row. Four different widths. With 12 one-unit options, 75 two-unit combinations and over 250 three-unit combinations, configuration is where bespoke begins.

TRINITY COOLING

Revel in the trinity of food preservation: three zones, three precision sensors, calibrated every second. Fortified by an exposed air tower, you can conquer humidity levels and customize the temperature of each zone to your deepest desires.

REMOTE ACCESS¹

Open door. Power outages. Filter changes. Connect to WiFi for real-time notifications and control your columns from anywhere. Tap and swipe on both iOS and Android devices.¹


ECLIPTIC LIGHTING

Live beyond the shadow. Abandoning the dark spots cast by dated puck lighting, over 650 LEDs frame and fill your column, coming alive at a touch of the controls. Each zone awakens and pulses as you mold your column to your desires.

DARING OBSIDIAN INTERIOR

Inspired by the beauty of volcanic glass, this industry-exclusive dark finish erupts with reflective, high-contrast style. Stop the whitewashing. Reject the unfeeling, lifeless vessel of harsh steel. Let fine foods and beverages emerge from the interior of your columns like vibrant art, begging to be devoured.

¹ Appliance must be set to remote enable. WiFi & App required. Features subject to change. For details and privacy, visit jennair.com/connect.



CARBON24L

CARBON 24" CUTS BY JENNAIR LEATHER PANEL

Indulge in touchable textures that bring the warmth and premium feel of leather into the vertical surfaces of the kitchen. Each of the four special edition designs is swathed in seductive Italian leather. Carbon, Cognac, Croc and Caviar rewrite the rule of what can be touched in your kitchen.

FEATURES

CARBON LEATHER

Hand-selected aniline leather panels crafted from natural, supple leather grades. This classic black finish fits with any kitchen design.

CHOOSE A CUSTOM HANDLE


Choose a JennAir® RISE™ or NOIR™ Design Expression handle to match your appliances or mount a one-of-a-kind handle crafted by an artist.¹

PAIRS WITH JENNAIR®

COLUMN REFRIGERATION

Cuts By JennAir® leather panels complement JennAir® column refrigerators with a Burlesque interior, adding further depth and intrigue to each piece.

¹ Accessory handles sold separately.



CROC24L

CROC 24" CUTS BY JENNAIR LEATHER PANEL

Indulge in touchable textures that bring the warmth and premium feel of leather into the vertical surfaces of the kitchen. Each of the four special edition designs is swathed in seductive Italian leather. Carbon, Cognac, Croc and Caviar rewrite the rule of what can be touched in your kitchen.

FEATURES

CROC LEATHER

Authentic textured leather that emulates crocodile skin in a burgundy color with a secondary tone that adds depth to the finish. A bold, provocative option that stands out regardless of its surroundings.

CHOOSE A CUSTOM HANDLE

Choose a JennAir® RISE™ or NOIR™ Design Expression handle to match your appliances or mount a one-of-a-kind handle crafted by an artist.¹

PAIRS WITH JENNAIR®

COLUMN REFRIGERATION

Cuts By JennAir® leather panels complement JennAir® column refrigerators with a Burlesque interior, adding further depth and intrigue to each piece.

¹ Accessory handles sold separately.



CAVIAR24L

CAVIAR 24" CUTS BY JENNAIR LEATHER PANEL

Indulge in touchable textures that bring the warmth and premium feel of leather into the vertical surfaces of the kitchen. Each of the four special edition designs is swathed in seductive Italian leather. Carbon, Cognac, Croc and Caviar rewrite the rule of what can be touched in your kitchen.

FEATURES

CAVIAR LEATHER

Rich black leather tipped with pewter ink creates a two-toned effect that plays with the light.

CHOOSE A CUSTOM HANDLE

Choose a JennAir® RISE™ or NOIR™ Design Expression handle to match your appliances or mount a one-of-a-kind handle crafted by an artist.¹

PAIRS WITH JENNAIR®

COLUMN REFRIGERATION

Cuts By JennAir® leather panels complement JennAir® column refrigerators with a Burlesque interior, adding further depth and intrigue to each piece.

¹ Accessory handles sold separately.







24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23³/₄" (W) x 83⁷/₁₆" (H) x 23¹¹/₁₆" (Depth without door panels/handles)

Choose one of following configuration to match your kitchen design.

Base Unit (Panel Ready)	Base Unit+Stainless Panel Kits			
	RISE™ Stainless Panel	NOIR™ Stainless	Euro-Style Stainless Panel	Pro-Style® Stainless Steel Panel
Column refrigerator JBRFR24IGX, JBRFL24IGX, ALOVE24RRC				
	LH: JKCPL241GL RH: JKCPR241GL	LH: JKCPL241GM RH: JKCPR241GM	LH: JKCPL241GS RH: JKCPR241GS	LH: JKCPL241GP RH: JKCPR241GP

OPTIONAL ACCESSORIES FOR CUSTOM OVERLAY DESIGNS

RISE™ STAINLESS HANDLE KIT

- W11220303
- For use with Custom Overlay panels
- Quantity - One handle per kit

NOIR™ STAINLESS HANDLE KIT

- W11220302
- For use with Custom Overlay panels
- Quantity - One handle per kit





EURO-STYLE HANDLE KIT COLUMNS

- W11220300
- For use with Custom Overlay panels
- Quantity - One handle per kit

PRO-STYLE® HANDLE KIT COLUMNS

- W11220299
- For use with Custom Overlay panels
- Quantity - One handle per kit

JOIN KITS (FOR MULTIPLE UNIT INSTALLATIONS)

			
Handle-to-handle join kit (JAJ13HSS)	Handle-to-hinge join kit (JAJ11HSS)	Hinge-to-handle join kit (JAJ12HSS)	Burlesque Handle-to-handle join kit (JAJ14JSS)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

W11356517B




24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23³/₄" (W) x 83⁷/₁₆" (H) x 23¹¹/₁₆" (Depth without door panels/handles)

PRODUCT DIMENSIONS



*Add 1" (2.5 cm) to the height dimension when leveling legs are fully extended.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.




24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE


JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23³/₄" (W) x 83⁷/₁₆" (H) x 23¹/₁₆" (Depth without door panels/handles)

PRODUCT DIMENSIONS



FRONT VIEW



TOP VIEW

DIMENSION	DESCRIPTION	JBZFR24IGX JBZFL24IGX ALOVE24RRC
A	Height of door handle	
	RISE™ Stainless	57 ¹⁵ / ₁₆ " (147.2 cm)
	NOIR™ Stainless	40 ⁵ / ₈ " (103.2 cm)
	Euro-Style Stainless	50 ¹ / ₁₆ " (127.1 cm)
	Pro-Style® Stainless	45 ⁹ / ₁₆ " (115.7 cm)
	Custom panel (3/4" thick)	** **
B	Height to top of door handle	
	RISE™ Stainless	70 ³ / ₄ " (179.7 cm)
	NOIR™ Stainless	68 ¹ / ₁₆ " (174.5 cm)
	Euro-Style Stainless	68 ⁵ / ₁₆ " (173.4 cm)
	Pro-Style® Stainless	66 ¹ / ₁₆ " (167.7 cm)
	Custom panel (3/4" thick)	** **
C	Width from side of refrigerator to handle – door fully open 115°	13" (33 cm)
D	Width from side of refrigerator to handle – door open 90°	5" (12.7 cm)
E	Depth with handle	
	RISE™ Stainless	26 ⁵ / ₈ " (67.7 cm)
	NOIR™ Stainless	26 ⁹ / ₁₆ " (67.5 cm)
	Euro-Style Stainless	26 ⁹ / ₁₆ " (67.4 cm)
	Pro-Style® Stainless	27 ¹ / ₈ " (68.9 cm)
	Custom panel (3/4" thick)	** **
F	Depth with door	24 ¹ / ₂ " (62.2 cm)

**For custom panel models, this depends on handle chosen.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.




24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23 $\frac{3}{4}$ " (W) x 83 $\frac{7}{16}$ " (H) x 23 $\frac{1}{16}$ " (Depth without door panels/handles)

OPENING DIMENSIONS



†24" with 24" trim kit.




24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE


JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23 $\frac{3}{4}$ " (W) x 83 $\frac{7}{16}$ " (H) x 23 $\frac{11}{16}$ " (Depth without door panels/handles)



water supply location
under unit
(accessible behind air grille)

TOP VIEW - CABINET OPENING



water supply location behind unit
(also approved for electrical supply)

FRONT VIEW - CABINET OPENING

ELECTRICAL SUPPLY LOCATION

- Lighter yellow area indicates electrical supply located in a cabinet or accessible space above the unit opening.
- Power cord length is 9' and originates from the front right corner of the unit.
- There is room for a surface mount electrical outlets within the top 3 $\frac{1}{2}$ " of the opening.
- Darker yellow area indicates the electrical supply location within the top of the opening.
- Outlet should be located near the center of the allowable area for easy connection and disconnection after installation.

WALL WATER SUPPLY LOCATIONS

- Water outlet area shown in blue.
- Water outlet area is also approved for the electrical outlet location.
- Outlet area width and height corresponds to a 3/4" deep recessed area found on the back of all unit.
- Targeting the left side of the allowable area allows for additional water line routing flexibility and easier water line management under the unit.

FLOOR WATER SUPPLY LOCATIONS

- Floor access is available through the open space behind the air grille.
- The area available is shown in blue and is limited in size by the compressor compartment on the right and leveling assembly on the left.
- The height of the open space above the access area is 11" high which makes drilling water lines access holes through floor after installation possible.



24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L,
COGNAC24L, CROC24L and CAVIAR24L

23³/₄" (W) x 83⁷/₁₆" (H) x 23¹¹/₁₆" (Depth without door panels/handles)

ELECTRICAL REQUIREMENTS

WARNING



Electrical Shock Hazard

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

115 V, 60 Hz, AC only, 15 A or 20 A fused, grounded circuit is required. A dedicated circuit is recommended. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

WATER PRESSURE REQUIREMENTS

A cold water supply with water pressure between 40 and 120 psi (207 kPa and 827 kPa) is required to operate the ice maker. Call a licensed, qualified plumber with any questions about the water pressure.

REVERSE OSMOSIS WATER SUPPLY

A reverse osmosis system may be used provided that the water pressure from the filtration system meets the required water pressure requirements.

JennAir® Columns feature an auto-bypass water filtration system. To use your product with a reverse osmosis water filtration system, simply remove the water filter from the product.

LOCATION REQUIREMENTS

WARNING



Explosion Hazard

Keep flammable materials and vapors, such as gasoline, away from refrigerator.

Failure to do so can result in death, explosion, or fire.

Floor must be able to support the product's total weight of more than 600 lb (272 kg), including the door panels and contents of the product. Flooring under product must be at the same level as the room. Face of cabinetry must be plumb.




24" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JBRFR24IGX, JBRFL24IGX, ALOVE24RRC, CARBON24L, COGNAC24L, CROC24L and CAVIAR24L

23³/₄" (W) x 83⁷/₁₆" (H) x 23¹¹/₁₆" (Depth without door panels/handles)



FRONT VIEW


WOOD PANEL GUIDE

⚠ CAUTION

Pinch Hazard

Installation of door panels with less than a ³/₈" (0.95 cm) gap between the door panel and the adjacent cabinet increases the risk of potential pinching.

MODEL	FLUSH WIDTH (A)
24"	23 ³ / ₄ " (60.3 cm)



Thickness (B)	3/4" (1.9 cm) max.
Weight	60 lbs. (27.2 kg) max.
Height (C)	79 ⁷ / ₈ " (202.9 cm)